

QUICK REFERENCE GUIDE

MODEL 1555 (832 Style Keypad)

Arming: Enter [4 digit code]. [*], [0] if Quick Arming is available.

Disarming: Enter [4 digit code].

Entry Delay Off : Enter [*], [9], [4 digit code]. This will arm the entire system in “Night Arm” and take away the entry delay time from all doors making them instant. The Motion Detectors will be off. The red armed light will flash the entire time the system is in this mode. OR
Enter [*], [9], [4 digit code], [*], [1]. This will do the same as above except that the Motion Detectors will be on. The red armed light will flash the entire time the system is in this mode.

Zone Bypassing: Enter [*], [1], [Two digit Zone number(s) (01-08) you want bypassed], [#]. Then arm the system. When system is disarmed all bypassed zones will reset to normal.

Additional Codes: Enter [*], [5], [4 digit master code], [Two digit code slot 01-32], [enter 4 digit code desired for that slot]. To change codes repeat steps above. To erase a code repeat steps above except enter [*] instead of a 4 digit code. To leave this mode enter [#].

Door Chimes: Hold “Chime” Button on keypad down for two seconds.

Fire Reset: To silence the siren enter [#], [4 digit code]. The fire circuit will need to be reset. To reset the fire circuit hold the “Reset” button on the keypad down for two seconds.

Alarm Memory: After every alarm the “Memory” light on the keypad will be on. To find out which zone was in alarm press [*], [3]. One or more of the zone lights will come on to indicate which zone was in alarm. The “Memory” light will stay on until system is rearmed.

System Testing: Call the monitoring station at (800) 631-2299, give them your account # and passcode. Tell them you want your system on test for about 15 minutes. Set off the alarm for about 20 seconds, disarm with your 4 digit code and then call the monitoring station to make sure your signals were received.

Smoke Testing: Call the monitoring station at (800) 631-2299, give them your account # and passcode. Tell them you want your system on test for about 15 minutes. Now blow smoke into the smoke detector, maybe with a cigarette or something and it should set off the alarm. Let it go for about 20 seconds, disarm with your 4 digit code and then call the monitoring station to make sure your signals were received.

Change Mastercode: Enter [*], [5], [Old Master Code], [40], [New Master Code], [#].

System Clock: Enter [*], [6], [Master Code], [1], [Military Time], [Date], [#], [#].